

# TECHNICAL DATA

	C 100	C 200	C 300	C 2
Machine speed (cartons/min.)	100	200	300	230
Connected load (kW)	1,75	5,0	5,0	3,75
Average power consumption (kW)	1,4	3,8	3,8	2,6
Air pressure consumption (Nm <sup>3</sup> /h) (depending on machine design)	3,5...6	3,5...6	3,5...6	3,5...6
Net weight (kg) (depending on machine design)	800	2 600	2 600	1 200
Carton size range (mm) min. max.	AxBxH 30x12x70 100x85x150	AxBxH 30x12x65 100x85x180	AxBxH 30x12x65 75x75x150	AxBxH 30x12x70 75x60x120
Carton quality in accordance with DIN 53121 (weight g/m <sup>2</sup> )	200 to 500	200 to 500	200 to 500	200 to 500
Floor space (mm) without magazines with magazines and leaflet folder	LxBxH 2150x1200x1550 2550x1400x1550	LxBxH 4700x1800x2000	LxBxH 1600x1200x1500 1900x1600x1500	LxBxH 1600x1200x1500 1900x1600x1500
<b>Blister magazine</b> Infeed speed into 1 magazine Infeed speed into 2 magazines Stacking height (Adjustment via pre-selector)	up to 300 Blisters/min. — 1–10 (12) Blisters/carton	up to 300 Blisters/min. up to 600 Blisters/min. 1–10 (12) Blisters/carton	up to 300 Blisters/min. up to 600 Blisters/min. 1–10 (12) Blisters/carton	up to 300 Blisters/min. up to 600 Blisters/min. 1–10 Blisters/carton
<b>Leaflets</b> Format (mm) min. max.	100x80 210x300	100x80 210x300	100x80 210x300	100x80 210x300
Folding length (mm) min. max.	100 210	100 210	100 210	100 210
Paper quality (g/m <sup>2</sup> )	40...70	40...70	40...70	40...70

Techn. improvements and changes of technical data subject to modifications.