

New **NEC** Ribbon Blenders



Standard Features:

Interior: 304 or 316 Stainless Steel, with #4 finish

Exterior: 304 Stainless Steel, with #4 finish

Center discharge: Butterfly valve

Motor: SEW or Nord

Safety grates with limit switches

Working Capacity (CuFt)	1	2.5	5	10	15	25	35	50	75	100
Motor HP	1	1.5	3	5	5	7.5	10	15	20	25
RPM	54	54	46	36	36	36	36	32	30	30
Discharge Diameter (inches)	4	4	4	4	6	6	6	8	8	8
Overall Length (inches)	33	46	50	64	70	80	90	104	114	137
Overall Width (inches)	16	19	23	28	32	34	38	41	48	51
Overall Height (inches)	34	39	43	72	69	75	72	77	81	91
Tub Length (inches)	18	26	33	43	48	59	59	78	89	98
Tub Width (inches)	11	14	18	22	25	30	35	36	42	45
Tub Height (inches)	13	18	22	26	29	33	39	40	47	51
Discharge Shroud to Floor (inches)	10	23	28	34	30	35	32	30	26	28

* All measurements are approximate

**Worldwide Leading Supplier of New, Used & Rebuilt
Processing & Packaging Machinery**

UNION
CONFECTIONERY MACHINERY

✉ sales@unionmachinery.com
 🌐 www.unionmachinery.com
 📞 718.585.0200

UNION
STANDARD EQUIPMENT