

**1.2 Specifications (continued)**

<b>Power supply</b>	Please refer to rating plate on machine.
<b>Air supply</b>	Please refer to rating plate on machine.
<b>Output</b>	Please refer to rating plate on machine.

**Central adjustable chute & pick-up**

- Pharmaceutical caps (diameter must be larger than height)
  - Type 400 and child-proof
- Min: 18 mm                      Max: 75 mm

OR

**Individual adj. chute with fixed pick-up**

- Cosmetic caps (max. height 1 3/8" or 35 mm)
  - Type 400 and child-proof
- Min: 22 mm                      Max: 127 mm exterior

## 1.2 Specifications

### Size of containers

- Diameter: Min: 3/4" (18 mm) Max: 6 1/4" (158 mm)
- Height (Total): Min: 2 1/2" (63 mm) Max: 5" (127 mm) w. single belt
- Min: 2" (51 mm) w/slim belt Max: 12" (305 mm) w. double belt
- Format: Round, rectangular or oval

### Size of caps

- Diameter: Min: 3/4" (18 mm) Max: 3" (75 mm)  
(Up to 5"/127mm on request)
- Type: Screw cap, snap cap or child-proof cap (in plastic or metal)
- Clearance between tightening disks: Max. 6" (150 mm)

### Overall dimensions of the machine (See Layouts with options)

- Length: 3 ft (0.91 m)
- Width: 3 ft (0.91 m)
- Height: 5 ft (1.52 m)

### Cap elevator with air reject

- Cap diameter: Min 3/4" (18 mm) Max: 3" (75 mm) exterior,  
(Up to 4 1/4" (110mm) ext. on request)  
Min. thickness 1/4" (6 mm), Max. thickness 3/4" (19 mm)
- Output: 200 – 220 CPM (33/45 cap type 400 plastic)  
200 – 300 CPM (33/45 child-proof in plastic)  
200 – 220 CPM (33/45 mm cap type 400 metal)
- Hopper capacity: 3 cu. ft. (0.08 cu. m)
- Air Supply: Please refer to rating plate on machine.

### Vibratory bowl

- Diameter: Min 24" (610 mm) Max: 30" (770 mm)
- Output: Approx. 80/min for 24" or approx. 100/min for 30"
- Bulk Hopper Capacity: 4 cu. ft (0.11 cu. m)
- Format: Cosmetic caps